

台式焊锡机系列
Desktop Soldering Machine Series

八轴双站式焊锡机
8-Axis Dual-Station Soldering Machine



扫码查看公众号



扫码查看视频号

本文件版权归嘉孚朗机器人设备(苏州)有限公司所有, 翻版必究。

All rights reserved by JEFLON Robot Equipment (Suzhou) Co., Ltd. Reproduction is strictly prohibited.

01 产品介绍 Product Introduction

WB

台式焊锡机
Desktop Soldering
Machine

2Y

双工位
Two-
station

3341

产品序列号
Product Series No

RS

R轴
R-axis



1、一人操作多机，减少人力、提升品质；

1. Single-operator multi-machine control — reduces labor costs and improves product quality.

2、大功率150W德式银系列发热系统，烙铁头专利技术定位设计；

2. High-power 150W German silver heating system with patented soldering tip positioning technology.

3、双路焊锡模组，双站连体设计，效率双倍提升；

3. Dual soldering modules with a two-station integrated design, doubling efficiency.

4、JEFLON焊锡专用控制系统，图形显示 阵列编程、焊点工艺参数整体修改、中途暂停点继续工作功能，编程方便快捷；

4. JEFLON soldering control system — supports graphical array programming, batch modification of soldering parameters, and pause/resume functionality for easy and efficient programming.

5、龙门式机械手采用进口运动组件，X/Y 轴运行速度可达：600mm/s,重复精度可达±0.02mm；

5. Gantry-type robotic arm equipped with imported motion components; X/Y-axis speed up to 600 mm/s and repeat accuracy up to ±0.02 mm.

6、预留多组数据IO接口，可控制治具及与 机械手联机自动运行；

6. Equipped with multiple sets of data I/O interfaces, enabling fixture control and automated operation in conjunction with robotic arms.

7、可连接视觉定位系统，自动补偿坐标 数据、精准定位、提升焊锡良率(选配项)。

7. Can be connected to a vision positioning system for automatic coordinate compensation, precise positioning, and improved soldering yield (optional).

产品型号/Product Model	WB-2Y-3341RS		
外形尺寸/Dimensions	W1270*D750*H900mm 此处外形尺寸仅限参考，以实物的实际尺寸为准。 Dimensions for reference only; subject to the actual product.		
工作区域/Working Area	W250*L400mm*2		
各轴行程/Travel of Each Axis	X300/Y300/Z100mm/R360°*2		
运行速度/Speed	X/Y:0.1-600mm Z:0.1-300m/s R0.1-300°/s		
重复精度/Repeatability	X/Y/Z: ±0.02mm, R轴: ±0.2°		
承重范围/Load Capacity	8KG/Y轴单工作台/8 kg per Y-axis workstation		
输入电压/Input Voltage	220V	输入气压: Input Air-pressure	4-8kg/cm
示教方式/Teaching Method	使用编程器示教/Programming via handheld teaching pendant		
文件容量/Storage Capacity	可预存1000组程序，每组可编辑8000条指令 Up to 1,000 programs; each program supports up to 8,000 commands		
适用锡丝/Applicable Solder Wire	标准送丝机; φ0.5-1.2mm,破锡型送丝机: φ0.8-1.2mm Standard wire feeder: φ0.5–1.2 mm Break-type wire feeder: φ0.8–1.2 mm		
发热模组/Heating Module	单支发热芯功率: Single heating core power	150W	
	温度范围: Temperature range	50-500°C	
温控模组/Temperature Control Module	控温精度: Control accuracy	2°C (空载状态)	
	温度补偿范围: Temperature compensation range	±50°C	

感谢支持

Thanks for the support



嘉孚朗机器人设备（苏州）有限公司

JEFLON Robot Equipment (Suzhou) Co., LTD.

中国·苏州·高新区真北路88号高端智能装备制造园5幢501

Room 501, Building 5, High-end Intelligent Equipment Manufacturing Park,
No. 88 Zhenbei Road, Suzhou High-tech Zone, Suzhou, Jiangsu, China

网址: www.jeflon.com 电话: 13913157898

Website: www.jeflon.com Phone: 13913157898